



Office & Work :  
Plot No. : G-1064, G.I.D.C. Lodhika (Metoda)  
Rajkot (Gujarat) INDIA - 360021

Phone : +91 -2827-287201  
E- mail : info@microfusioncast.com  
Web : www.microfusioncast.com

### INSPECTION CERTIFICATE

F-QA-02/Rev-03/Date: 01/09/2018

THIS CERTIFICATE HAS BEEN PREPARED AS PER EN 10204 : 2005 (Type 3.1)

Customer : **JC VALVULAS INDIA PVT LTD**  
Metal Spe. : **DIN EN 10213 - 1.0619 - 2016-10 & JC-MDS-641, Rev No. 0**

Melting Media : Air Melting Through Electric Induction Furnace  
Mfg. Process : Investment Casting By Lost Wax Process

TC No.: GT/25-26/1125 - 1.0619

Date :26/02/2026

Inv. No. : GT/25-26/1125

Date :26/02/2026

Heat Treatment : 1) Quenching : Heated at 920 °C for 2 Hr. and Water Quench. 2) Tempering : Heated at 675 °C for 4 Hr. and Furnace Cool.

#### Spectro Chemical Analysis

HEAT NO.	C %	Si %	Mn %	S %	P %	Cr %	Ni %	Mo %	Cu %	V %	RE	CE %			
MIN	0.180		0.500												
MAX	0.230	0.600	1.200	0.020	0.030	0.300	0.400	0.120	0.300	0.030	1.000	0.430			
B608	0.182	0.354	0.850	0.008	0.015	0.103	0.059	0.005	0.026	0.009	0.202	0.353			
B609	0.199	0.397	0.880	0.009	0.016	0.112	0.094	0.015	0.031	0.007	0.206	0.381			
B639	0.207	0.368	0.880	0.009	0.017	0.097	0.064	0.007	0.027	0.010	0.205	0.383			
B658	0.184	0.352	0.940	0.008	0.016	0.107	0.070	0.008	0.024	0.008	0.217	0.372			

#### Mechanical Properties

#### Impact Test

#### Hardness Test

HEAT NO.	Tensile Strength		Yield Strength (0.2% Offset)		% Elongation (GL 25mm)	Impact Test(10mm X 10mm X 55mm) CVN 2mm at -29 °C In Joule				Hardness (HBW)	
	MPa	MPa	MPa	MPa		1	2	3	AVG.		
MIN	420.00		240.00		22.00	27.0					
MAX	600.00					1	2	3	AVG.	225	
B608	519.52		325.91		39.20	38.0	36.0	36.0	36.6	159	
B609	521.07		340.95		34.40	38.0	34.0	32.0	34.6	144	
B639	559.67		350.60		39.20	38.0	36.0	32.0	35.3	150	
B658	513.07		319.46		36.80	38.0	36.0	36.0	36.6	144	

#### Dispatch Detail

#### Special Note

Sr. No.	Description / Drawing No. - Revision No.	Cust. Part ID	Heat No.	Dispatch Quantity	PO No.	Line No.	
1	2" (DN50) FIG -540 PN40 - ADAPTER (CS)-M/C, Drg. No. : 0540050LM-07	L0540A050-037	B608	21	JCCMP-2526-01879	18	Marking on Casting : • Heat No. punch on Casting. • Foundry Logo. <div style="border: 1px solid blue; padding: 5px; display: inline-block;"> <p style="color: blue; font-weight: bold;">JC Valvulas India Pvt. Ltd.</p> <p style="color: blue;">Chennai, Tamil Nadu, India</p> <p style="color: blue; font-style: italic;">Verified &amp; Accepted</p> <p style="color: blue;">Q.A. <i>R. D. K.</i></p> </div>
2	2" (DN50) FIG -540 PN40 - ADAPTER (CS)-M/C, Drg. No. : 0540050LM-07	L0540A050-037	B609	29	JCCMP-2526-01879	18	
3	2" (DN50) FIG -540 PN40 - ADAPTER (CS)-M/C, Drg. No. : 0540050LM-07	L0540A050-037	B639	16	JCCMP-2526-01879	18	
4	2" (DN50) FIG -540 PN40 - BODY (CS)-M/C, Drg. No. : 0540050CM-08	C0540A050-037	B658	14	JCCMP-2526-01879	10	

Total Quantity : 80

Foundry Identification : (M)

\* We, hereby certify that the items mentioned above are Manufactured, Stamped, Tested and Inspected in accordance with applicable material specifications DIN EN 10213 - 1.0619 - 2016-10 & JC-MDS-641, Rev No. 0 and was found to meet the requirements.  
 \* Certified that above mentioned casting is free from Radioactive Contamination.  
 \* Found satisfactory as per MSS-SP-55 TYPE II TO XII CATEGORY A AND B ONLY  
 \* Mechanical Test Specimens prepare & tested accordingly DIN EN ISO 6892-1:2019  
 \* Impact Test Specimens prepare & tested accordingly EN ISO 148-1.  
 \* Casting confirms to NACE MR 0175:2021/ISO 15156 :2020 & NACE MR 0103:2015/ISO 17945:2015.  
 \* Approved & Certified according to PED 2014/68/EU - Annexure 1 Chapter 4.3 & AD 2000 - Merkblatt WO by Notified body for pressure equipment directive of TUV NORD



For, Microfusion Cast & Alloys

Jignesh Patel (Director)  
Authorised By